



Calibration roller KWO-250



The calibration roller for fixed assembly...

**Our champion:
The lightest calibration roller
on earth - till DN 250 !**



... or for mobile application !

What is calibration roller KWO-250?

An ingenious **roller for the calibration** of impregnated hose liners especially for **sewer rehabilitation**.

Advantages of calibration roller KWO-250

- light and compact construction
- main pillars removable or fixed
- feed and return run
- roller gap adjustable
- high operational safety
- also designed for fixed assembly (optional guide rail extension)

Technical data

Voltage	230 V / 50 Hz
Power	110 W
Rolling speed	0 - 5 m/min
Rolling gap width	0 - 90 mm
Useable gap width	max. 400 mm
Weight	approx. 52 kg

Subject to technical amendments.



Calibration roller KWO-250

Are you interested?

Yes, I/we would like

a non-binding presentation
 further information

an offer
 to order

Company	_____	Fon	_____
Person	_____	Fax	_____
Address	_____	e-Mail	_____
Country/PC/Place	_____		
Branche			
Fire brigade	<input type="checkbox"/>	Pipe cleaning	<input type="checkbox"/>
Civil defence	<input type="checkbox"/>	Other	<input type="checkbox"/>

Please send us your information, we will contact you as soon as possible.